

# THOROSEAL® FOUNDATION COATING

Waterproof cement-based coating for exterior below-grade concrete and masonry



CONSUMER PRODUCTS

## Features and Benefits:

- Heavy, cement-based coating, bonding well with concrete and masonry substrates.
- Protects building interiors from dampness and moisture damage.
- Resistant to both positive and negative hydrostatic pressure.
- Will not "blow off" exposed side of wall.
- Breathable; allows interior moisture to escape without damaging coating.
- Locks deep into pores and voids to become part of the wall when fully cured.
- Gray in color to blend into cement block and concrete walls.
- Resistant to mold and mildew.
- Apply with a push broom or 6" masonry brush.
- Can also be mixed with clean washed sand and trowel-applied as a superior waterproofing coating.
- Can be used above grade, but not intended as a decorative finish coat.
- Comes in dry powder form; Acryl® 60 can be added to mixture.
- Cleans up with soap and water immediately after use.

## Warranty:

- Against defective product. Full warranty details at [ThoroProducts.com](http://ThoroProducts.com).

## Recommended for:

- Concrete
- Masonry
- Basement Walls
- Foundation and Retaining Walls

## Must add ACRYL® 60 to achieve peak product performance.

- Improves adhesion, bonding, and curing.
- Adds flexural strength, overall durability and resistance to freeze/thaw.



## Yield per 50-pound bag:

- Base coat: 225 square feet at 1/16 inch dry-film thickness
- OR Top coat: 450 square feet at 1/32 inch dry-film thickness
- Coverage will vary depending on surface texture and porosity.

Ship weight is gross U.S. pounds



Item Number	Color	Single Unit Net Wt.	Single Unit UPC Code	Unit Ship Weight	Units per Pallet	Pallet Ship Weight
T1180	Concrete/Dark Gray	50 lb. Sack	0 80492 01180 7	51	48	2,448

Satisfactory results depend on selection of suitable product for intended use and compliance with instructions for surface preparation and application.

Thoro Consumer Products • BASF Construction Chemicals, LLC • 23700 Chagrin Blvd. • Cleveland, Ohio 44122

phone 216-839-7171 or 866-518-7171 • fx 216-839-8833 or 866-494-8833 • [ThoroProducts.com](http://ThoroProducts.com)