

# THOROSEAL® WATERPROOF CEMENT-BASED COATING

For a durable waterproof barrier on interior or exterior concrete and masonry



CONSUMER PRODUCTS

## Features and Benefits:

- Waterproofs and protects building interiors from dampness, moisture, or seepage.
- Ideal for interior or exterior, above or below grade; vertical, overhead and non-traffic bearing surfaces.
- Locks water out or holds it in by actually becoming part of the wall.
- Fills and seals pores and voids to correct surface irregularities.
- NSF approved (white or gray products), use in potable water tanks.
- Resistant to mold and mildew.
- Compatible with a wide range of architectural coatings and textured finishes.
- Available in white or gray.
- Comes in dry powder form; must add Acryl® 60 to mixture.
- Cleans up with soap and water immediately after use.

## Warranty:

- Against defective product. **Two Coats Necessary.** Must NOT be applied to painted surfaces.
- Full warranty details at [ThoroProducts.com](http://ThoroProducts.com).

## Recommended for:

- Cast-in-Place Concrete
- Pre-cast Concrete
- Brick
- Common Block
- Stucco
- Unglazed Terra Cotta
- Porous Stone
- Guniting
- Other Masonry Substrates

## Must add ACRYL® 60 for peak product performance.

- Improves adhesion, bonding, and curing.
- Adds flexural strength, overall durability, and resistance to freeze/thaw.



White finish



Gray finish

## Yield per 50-pound bag:

- Base coat: 225 square feet at 1/16 inch dry-film thickness
- OR Top coat: 450 square feet at 1/32 inch dry-film thickness
- Coverage will vary depending on surface texture and porosity.

Ship weight is gross U.S. pounds

Item Number	Color	Single Unit Net Wt.	Single Unit UPC Code	Unit Ship Weight	Units per Pallet	Pallet Ship Weight
T4002	White	50 lb. Sack	0 80492 04002 9	51	48	2,448
T4003	White	60 lb. Pail	0 80492 04003 6	63	36	2,268
T1018	Gray	50 lb. Sack	0 80492 01018 3	51	48	2,448
T1019	Gray	60 lb. Pail	0 80492 01019 0	63	36	2,268



Satisfactory results depend on selection of suitable product for intended use and compliance with instructions for surface preparation and application.

Thoro Consumer Products • BASF Construction Chemicals, LLC • 23700 Chagrin Blvd. • Cleveland, Ohio 44122

phone 216-839-7171 or 866-518-7171 • fx 216-839-8833 or 866-494-8833 • [ThoroProducts.com](http://ThoroProducts.com)